P/N 220219A255

۲

ELECTRONIC CONTROL AIR CONDITIONER

READ AND SAVE THESE INSTRUCTIONS

۲

USE & CARE MANUAL

ROOM AIR CONDITIONER WARRANTY

Your product is protected by this warranty

Your appliance is warranted by Electrolux. Electrolux has authorized Frigidaire Consumer Services and their authorized servicers to perform service under this warranty. Electrolux authorizes no one else to change or add to any of these obligations under this warranty. Any obligations for service and parts under this warranty must be performed by Frigidaire Consumer Services or an authorized Frigidaire servicer.

	WARRANTY PERIOD	FRIGIDAIRE, THROUGH ITS AUTHORIZED SERVICERS, WILL:	THE CONSUMER WILL BE RESPONSIBLE FOR:
FULL ONE-YEAR WARRANTY	One year from original purchase date.	Pay all costs for repairing or replacing parts of this appliance which prove to be defective in materials or workmanship.	Costs of service calls that are listed under NORMAL RESPONSIBILITIES OF THE CONSUMER.*
LIMITED 2-5 YEAR WARRANTY (Sealed System)	Second through fifth years from original purchase date.	Repair or replace any parts in the Sealed Refrigeration System (compressor, condenser, evaporator and tubing) proves to be defective in materials or workmanship.	Diagnostic costs and any removal, transportation and reinstallation costs which are required because of service. Costs for labor, parts and transportation other than with respect to the Sealed Refrigeration System.
LIMITED WARRANTY (Applicable to the State of Alaska)	Time periods listed above.	All of the provisions of the full and limited warranties above and the exclusions listed below apply.	Costs of the technician's travel to the home and any costs for pick up and delivery of the appliance required because of service.

* NORMAL RESPONSIBILITIES OF THE CONSUMER	 This warranty applies only to products in ordinary household use, and the consulisted below. Proper use of the appliance in accordance with instructions provided with the produ. Proper installation by an authorized servicer in accordance with instructions provided with all local plumbing, electrical and/or gas codes. Proper connection to a grounded power supply of sufficient voltage, replacement of blor or defects in house wiring. Expenses for making the appliance accessible for servicing, such as removal of trim, not a part of the appliance when it was shipped from the factory. Damages to finish after installation. Replacement of light bulbs and/or fluorescent tubes (on models with these features) 	ct. with the appliance and in accordance wn fuses, repair of loose connections cupboards, shelves, etc., which are
EXCLUSIONS	 This warranty does not cover the following: CONSEQUENTIAL OR INCIDENTAL DAMAGES SUCH AS PROPERTY DAMAGES SUCH AS PROPERTY DAMAGES SUCH AS PROPERTY DAMAGES AND ANY BREACH OF THIS WRITTEN OR ANY IMPLIED WARRANT the exclusion or limitation of incidental or consequential damages, so this limitation of the exclusion or limitation of incidental or consequential damages, so this limitation of the exclusion or limitation of incidental or consequential damages, so this limitation of the exclusion or limitation of incidental or consequential damages, so this limitation of the exclusion or limitation of incidental or consequential damages, so this limitation of the exclusion or limitation of the exclusion or defects in workmanship or material household use. The consumer shall pay for such service calls. Damages caused by services performed by persons other than authorized Frigidair Frigidaire Genuine Renewal Parts; obtained from persons other than such servicers misuse, inadequate power supply or acts of God. Products with original serial numbers that have been removed or altered and cannot approximately approximately provide the provide that the provide the provide the provide that the provide the pro	TY. Note: Some states do not allow or exclusion may not apply to you. al, or for appliances not in ordinary re servicers; use of parts other than ; or external causes such as abuse,
IF YOU NEED SERVICE	 Keep your bill of sale, delivery slip, or some other appropriate payment record. The date period should service be required. If service is performed, it is in your best interest to obta warranty gives you specific legal rights. You may also have other rights that vary from warranty must be obtained by following these steps, in order: Contact Frigidaire Consumer Services or an authorized Frigidaire servicer. If there is a question as to where to obtain service, contact our Consumer Relations Frigidaire P.O. Box 212378 Augusta, GA 30917 B00-444-4944 	in and keep all receipts. This written n state to state. Service under this

Product features or specifications as described or illustrated are subject to change without notice. All warranties are made by Electrolux.

This warranty applies only in the 50 states of the U.S.A., Puerto Rico and Canada.

FOR SERVICE CALL 1-800-444-4944.

Product Registration

Record Your Model and Serial Numbers

Record in the space provided below the model and serial numbers. On all models, the serial plate is located on the outside of the cabinet.

Model No.

Serial No.

2

3

3

4

11

11

12


Register Your Product

The self-addressed PRODUCT REGISTRATION CARD should be filled in completely, signed and returned to the Frigidaire Company.

Contents

- Warranty
- Product Registration
- Normal Sounds
- **NOTE:** This USE & CARE MANUAL provides specific operating instructions for your model. Use the room air conditioner only as instructed in this USE & CARE MANUAL. These instructions are not meant to cover every possible condition and situation that may occur. Common sense and caution must be practiced when installing, operating, and maintaining any appliance.
- Important Safety Instructions
- 5-11 Using Air Conditioner
- 5-11 Air Conditioner Features
 - Care and Cleaning
 - Energy Saving Ideas
 - Avoid Service Checklist

Normal Sounds



Important Safety Instructions

NOTE The power supply cord with this air conditioner contains a current detection device designed to reduce the risk of fire.

Please refer to the section 'Operation of Current Device' for details.

In the event that the power supply cord is damaged, it cannot be repaired-it must be replaced with a cord from the Product Manufacturer.

Avoid fire hazard or electric shock. Do not use an extension cord or an adaptor plug. Do not remove any prong from the power cord.

Do not, under any

circumstances, cut,

remove, or bypass the

grounding prong.

Grounding type wall receptacle

Power supply cord with 3-prong grounding plug and current detection device

Read all instructions before using this air conditioner.

AWARNING For Your Safety

Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance. Read product labels for flammability and other warnings.

Awarning Prevent Accidents

To reduce the risk of fire, electrical shock, or injury to persons when using your air conditioner, follow basic precautions, including the following:

- Be sure the electrical service is adequate for the model you have chosen. This information
 can be found on the serial plate, which is located on the side of the cabinet and behind the
 grille.
- If the air conditioner is to be installed in a window, you will probably want to clean both sides of the glass first. If the window is a triple-track type with a screen panel included, remove the screen completely before installation.
- Be sure the air conditioner has been securely and correctly installed according to the separate installation instructions provided with this manual. Save this manual and the installation instructions for possible future use in removing or reinstalling this unit.
- When handling the air conditioner, be careful to avoid cuts from sharp metal fins on front and rear coils.

A WARNING Electrical Information

The complete electrical rating of your new room air conditioner is stated on the serial plate. Refer to the rating when checking the electrical requirements.

- Be sure the air conditioner is properly grounded. To minimize shock and fire hazards, proper grounding is important. The power cord is equipped with a three-prong grounding plug for protection against shock hazards.
- Your air conditioner must be used in a properly grounded wall receptacle. If the wall
 receptacle you intend to use is not adequately grounded or protected by a time delay fuse
 or circuit breaker, have a qualified electrician install the proper receptacle.
- Do not run air conditioner with outside protective cover in place. This could result in mechanical damage within the air conditioner.
- Do not use an extension cord or an adapter plug.

READ THIS SECTION BEFORE ATTEMPTING TO OPERATE AIR CONDITIONER.

Operation of Current Device



NOTE: Some plugs have buttons on the top.

The power supply cord contains a current device that senses damage to the power cord. To test your power supply cord do the following:


- 1. Plug in the Air Conditioner.
- The power supply cord will have TWO buttons on the plug head. Press the TEST button. You will notice a click as the RESET button pops out.
- 3. Press the RESET button. Again you will notice a click as the button engages.
- The power supply cord is now supplying electricity to the unit. (On some products this is also indicated by a light on the plug head).

NOTES:

- Do not use this device to turn the unit on or off.
- Always make sure the RESET button is pushed in for correct operation.
- The power supply cord must be replaced if it fails to reset when either the TEST button is pushed, or it cannot be reset. A new one can be obtained from the product manufacturer.
- If power supply cord is damaged, it CANNOT be repaired. It MUST be replaced by one obtained from the product manufacturer.

Air Conditioner Features ELECTRONIC CONTROL OPERATING INSTRUCTIONS

Before you begin, thoroughly familiarize yourself with the control panel and remote as shown below and all its functions, then follow the symbol for the functions you desire. **The unit can be controlled by the unit control alone or with the remote.**



Note: Please refer to separate remote control manual for additional operations. Battery Size: AAA

Warning: do not mix old and new batteries. Do not mix alkaline, standard (carbon-zinc), or rechargeable (nickel-cadmium) batteries.

۲

(�)

۲


Air Conditioner Features

(continued) TO TURN UNIT ON:

Gibson TEMP TEMP \$) <u>%</u> 0 ENERGY SLEEP TIMER TIMER CLEAN CHECK DO THIS: MED н FAN DR PRESS ON/ US \$ ()5 OFF BUTTON AN AUTO COOL AUTO TEMP LO

Note: The unit will turn on in the cool mode and high fan speed.

TO CHANGE TEMPERATURE SETTING:



NOTE: The following instructions represent the Unit Control, the same instructions can be used for the Remote Control.

YOU WILL SEE:



YOU WILL SEE:


YOU WILL SEE

THE SPEED CHOSEN:



Note: Tap or hold either up (\bigstar) or down (\checkmark) button until the desired temperature is seen on the display. This temperature will be automatically maintained anywhere between 62°F (17°C) and 86°F (30°C) for cooling mode. If you want the display to read the a ctual room temperature. See "To Operate on Fan Only" section on Page 8.

TO ADJUST FAN SPEEDS:







۲

(continued)

TO USE AUTO TEMP FEATURE:




Note: Fan starts at High Speed and adjusts to a slower speed as the room temperature dictates. For example if the room doesn't get too warm, it will stay at the slowest speed. If the room temperature rises quickly, such as a door being opened, it will automatically go to the highest speed. The fan speeds will re-adjust back to the slowest speed as the room returns to the original set temperature. Press the fan button to adjust the fan speed manually.



Note: Use this mode when the room is already cool below 65°F (18°C) but the room is slightly humid.


TO USE AUTO COOL:

YOU WILL SEE:



Note: In this mode when the room temperature is reached the compressor will shut off and after a few minutes the fan will switch to the lowest setting, (if a higher setting has been originally selected). When the compressor switches back to the cooling mode, then the fan speed will return to the original setting.


(continued)



۲


Note: Use this function only when cooling is not desired, such as for room air circulation You can choose any fan speed you prefer, except Auto Temp. During this function, the display will show the actual room temperature, not the set temperature as in the cooling mode.

TO USE THE ENERGY SAVER FEATURE:



Note: In this mode, the fan will continue to run for 3 minutes after the compressor shuts off. The fan then cycles on for 2 minutes at 10 minute intervals until the room temperature is above the set temperature, at which time the compressor turns back on and cooling stars.

TIMER: DELAY STOP / START FEATURE:



Note: For Delay Stop, the unit must be in the On position.

Note: For Delay Start, the unit must be in the Off position.


To adjust timer setting, tap or hold the UP arrow(
) or the DOWN arrow(
) to change delay timer at .5 hour increments, up to 10 hours, then at 1 hour increments up to 24 hours. The control will count down the time remaining until start (8, 7.5, 7, etc.). The Delay Start mode automatically selects cooling with maximum Fan Speed. The temperature maintained will be the same as previously set. To change the set temperature, press "COOL" then Up or Down arrows until the control will automatically change the display back to the hours remaining until the unit will start/stop. Turning the unit "ON" or "OFF" at any time will cancel the Delay Start/Stop function.

The Delay Start/Stop Feature will work until the unit either starts or stops. Once that happens the above steps have to be repeated again.

8




(continued)




۲

The Sleep Mode can be selected with a Heating or Cooling Mode. Note: In this "MODE" the selected temperature will increase by 2 degrees F, 30 minutes after the mode is selected. The temperature will then increase by another 2 degrees F after an additional 30 minutes. This new temperature will be maintained for 7 hours before it returns to the originally selected temperature. If this Mode is selected with Heat, the set temperature will decrease at the same time pattern. This ends the "Sleep" MODE and the unit will continue to operate as originally programmed. The "Sleep" MODE program can be cancelled at any time during operation by again pressing the "Sleep" button.



Note: This feature is a reminder to clean the Air Filter (See Care and Cleaning) for more efficient operation. The LED (light) will illuminate after 250 hours of operation. To reset after cleaning the filter, press the "Check Filter" button and the light will go off.



Note: When this feature is "ON", the electronic air purifier is energized to remove pollen and impurities from the air. To cancel this feature, press the Clean Air button (the LIGHT will turn off).

()

Air Conditioner Features (continued)

REMOTE SENSING/FOLLOW ME FEATURE









NOTE: Remote display is actual temperature at remote control only

۲


Note: This feature can be activated from the remote control ONLY, the unit must be in a cooling mode. To activate the remote sensing feature, point the remote control towards the unit and press the remote sensing button. Next, use the buttons to set the desired temperature at the remote. (Note that the set temperature will only be displayed on the unit itself). The LIGHT on the unit control will pulse to indicate it received the signal. The LIGHT on the remote control will pulse each time it sends a signal. It will continue to send this signal until the feature is deactivated by pressing the remote sensing button. If the unit does not receive the remote sensing signal during any 3 minute interval, the unit will beep to indicate the remote sensing mode has ended. The display on the remote control indicates the temperature at the remote ONLY. The unit display indicates the set temperature.

FAULT CODES



If the display reads "AS" or "ED", a sensor has failed. Contact your Authorized Frigidaire Service Center.

TO TURN UNIT OFF:



WARNING CODES



In the fan mode if "LO" or "HI" is displayed, this means the room temperature is outside the unit set points of 99°F/37°C (HI) or 32°F/0°C (LO).

YOU WILL SEE:





ADDITIONAL THINGS YOU SHOULD KNOW

Now that you have mastered the operating procedure, here are more features in your control that you should become familiar with.

- The "Cool " circuit has an automatic 3 minute time delayed start if the unit is turned off and on
- quickly. This prevents overheating of the compressor and possible circuit breaker tripping. The fan will continue to run during this time.



- The control will maintain the set temperature within 2 degrees Fahrenheit, between 62°F(17°C) and 86°F(30°C) degrees.
- The control is capable of displaying temperature in degrees Fahrenheit or degrees Celsius. To convert from one to the other and back, press and hold the "TEMP/TIMER" Up (▲) and Down (▼) buttons together for 3 seconds.


-	8 8 -	- 10- 1	
-		1000	A DOTTED A DOT

4-Air Directional Louvers

The 4-Way air directional louvers allow you to direct the air flow Up or Down and Left or Right throughout the room as needed. To adjust the air directional louvers side-to-side, use the center handles as you move it side-to-side.

(4-WAY)

Care and Cleaning



Clean your air conditioner occasionally to keep it looking new. Be sure to unplug the unit before cleaning to prevent shock or fire hazards.

Air Filter Cleaning

The air filter should be checked at least once a month to see if cleaning is necessary. Trapped particles in the filter can build up and cause an accumulation of frost on the cooling coils.

- Grasp the filter by the center and pull up and out.
- Wash the filter using liquid dishwashing detergent and warm water. Rinse filter thoroughly. Gently shake excess water from the filter. Be sure filter is thoroughly dry before replacing.
 Or, instead of washing you may vacuum the filter clean.

Cabinet Cleaning

- Be sure to unplug the air conditioner to prevent shock or fire hazard. The cabinet and front may be dusted with an oil-free cloth or washed with a cloth dampened in a solution of warm water and mild liquid dishwashing detergent. Rinse thoroughly and wipe dry.
 Never use harsh cleaners, wax or polish on the cabinet front.
- De sure te unier evenes water from the cloth before wining eround
- Be sure to wring excess water from the cloth before wiping around the controls. Excess
 water in or around the controls may cause damage to the air conditioner.
- Plug in air conditioner.

Winter Storage

If you plan to store the air conditioner during the winter, remove it carefully from the window according to the installation instructions. Cover it with plastic or return it to the original carton.

NOTE: To prevent rust or electrical connections from being damaged, store air conditioner in an upright position and a dry place.

Energy Saving Ideas



- Do not block air flow inside with blinds, curtains or furniture; or outside with shrubs, enclosures, or other buildings.
- The capacity of the room air conditioner must fit the room size for efficient and satisfactory
 operation.
- Install the room air conditioner on the shady side of your home. A window that faces north is best because it is shaded most of the day.
- Close the fireplace damper, floor and wall registers so cool air does not escape up the chimney and into the duct work.
- Keep blinds and drapes in other windows closed during the sunniest part of the day.
- Clean the air filter as recommended in the section "Care and Cleaning."
- Proper insulation and water stripping in your home will help keep warm air out and cool air in.
- External house shading with trees, plants or awnings will help reduce the air conditioner's work load.
- Operate heat producing appliances such as ranges, washers, dryers and dishwashers during the coolest part of the day.

Avoid Service Checklist

Before calling for service, review this list. It may save you time and expense. This list includes common occurrences that are not the result of defective workman-ship or materials in this appliance.

 \odot

۲

OCCURRENCE	SOLUTION
Air conditioner will not operate.	Wall plug disconnected. Push plug firmly into wall outlet.
	Plug Current Device Tripped. Press the RESET button.
	House fuse blown or circuit breaker tripped. Replace fuse with time delay type or reset circuit breaker.
	Control is OFF. Turn Control ON and set to desired setting.
Air from unit does not feel cold	Room temperature below 62°F (17°C). Cooling may not occur until room temperature rises above 62°F (17°C)
enough.	Temperature sensing element touching cold coil, located behind air filter. Straighten away from coil.
	Reset to a Lower temperature.
	Compressor shut-off by changing modes. Wait approximately 3 minutes and listen for compressor to restar when set in the COOL mode.
Air conditioner cooling, but room is	Outdoor temperature below 62°F (17°C). To defrost the coil, set FAN ONLY Mode.
too warm - ice forming on cooling coil behind decorative front.	Air filter may be dirty. Clean filter. Refer to Care and Cleaning section. To defrost, set to FAN ONLY Mode.
	Temperature is set too Low for night-time cooling. To defrost the coil, set to FAN ONLY Mode. Then, set Tem perature to a Higher setting.
Air conditioner cooling, but room is	Dirty air filter - air restricted. Clean air filter. Refer to Care and Cleaning section.
too warm - NO ice forming on cooling coil behind decorative front.	Temperature is set too High. Set temperature to a Lower setting.
J	Air directional louvers positioned improperly. Position louvers for better air distribution.
	Front of unit is blocked by drapes, blinds, furniture, etc restricts air distribution. Clear blockage in front of unit
	Doors, windows, registers, etc. open - cold air escapes. Close doors, windows, registers, etc.
	Unit recently turned on in hot room. Allow additional time to remove "stored heat" from walls, ceiling, floor and furniture.
Air conditioner turns on and off	Dirty air filter - air restricted. Clean air filter.
rapidly.	Outside temperature extremely hot. Set FAN speed to a faster setting to bring air past cooling coils more frequently.
Noise when unit is cooling.	Air movement sound. This is normal. If too loud, set to a slower FAN setting.
	Window vibration - poor installation. Refer to installation instructions or check with installer.
Water dripping INSIDE when unit is cooling.	Improper installation. Tilt air conditioner slightly to the outside to allow water drainage. Refer to installation instructions - check with installer.
Water dripping OUTSIDE when unit is cooling.	Unit removing large quantity of moisture from humid room. This is normal during excessively humid days.
Remote Sensing Deactivating Prematurely (Some Models).	Remote control not located within range. Place remote control within 20 feet & 180°, radius of the front of the unit.
	Remote control signal obstructed. Remove obstruction.
Room Too Cold.	Set temperature too low. Increase set temperature.
	Remote Sensing activated (on some models) and remote control located in Hot Spot - Relocate remote control or deactivate remote sensing.

If These Solutions Fail, Call 1-800-444-4944 For Frigidaire Service.

12

•